



2 Port HDMI 18G Splitter with Audio & Downscaling No.: 38230

Distribute $\mathsf{HDMI}^{\circledast}\,18\mathrm{G}$ signals across 2 displays while extracting digital or analogue audio

Description

Displays HDMI® signals across 2 displays simultaneously from one source device Supports resolutions up to 4K 60Hz 4:4:4, with additional support for HDR Extract digital and analogue audio from HDMI® for non-HDMI® amplifiers Features a neat switch for downscaling from 4K to 1080p 2 year warranty

The Lindy 2 Port HDMI® 18G Splitter with Audio is a multi-function solution for distributing high quality HDMI® signals across 2 displays simultaneously from one source device, while extracting digital or analogue audio separately. With support for resolutions up to 4K 60Hz 4:4:4 8bit, this splitter is great for creating eye-catching dual display digital signage in retail scenarios, displaying live video across two screens at event venues or distributing engaging multiscreen educational presentations at tradeshows.

The splitter also has separate optical and 3.5mm audio ports to easily extract audio from HDMI® to connect non-HDMI® amplifiers or soundbars, ideal for supporting video with immersive multichannel audio.

The additional ability to cascade this splitter up to three further levels allows for an extended HDMI® splitting experience, ideal for multi-screen situations such as informational broadcasting in airports, train stations or stock exchange offices. The splitters also features an integrated switch to downscale the input signal to Full HD, making installations with older displays hassle free while always ensuring the viewer receives the optimum picture from their display.

Technical details

Specifications

AV Interface: HDMI® Interface Standard: HDMI® 2.0 Supports Bandwidth: 18Gbps Maximum Resolution: 4096x2160@60Hz 4:4:4 8bit HDCP Support: 2.2 Supported Audio: Audio Pass-through LPCM 2CH Up to 7.1CH (Optical) Separate Audio Ports: 3.5mm (Female) Toslink (Optical) CEC Support: -Serial Interface: -

Special Features: Downscaler Function, EDID Emulation Connectors Input: HDMI® Type A (Female) Output: 2 x HDMI® Type A (Female), Toslink (Optical), 3.5mm (Female) Control: -Power: 5.5/2.1mm **Physical Properties** Dimensions (approx.) WxDxH: 120x14.4x63mm (4.72x0.57x2.48in) Housing Material: Metal Net Weight: 0.29kg (0.64lb) Operating Temperature: 0°C - 40°C (32°F - 104°F) Storage Temperature: -20°C - 60°C (-4°F - 140°F) Humidity: 20-90% RH (non-condensing) Power Requirements: 5VDC 1A Colour: Black **Miscellaneous** Packaging Type: Carton Box Packaging Dimensions: 206x64x117mm (8.11x2.52x4.61in) Gross Weight: 0.396kg (0.87lb) Warranty (Years): 2 Product Compliance: CE, FCC, RoHS, REACH & California Proposition 65 Package Contents 2 Port HDMI® Splitter with Audio Multi-Country Power Supply (UK, EU, US & AUS) Lindy Manual **Purchasing Information** No.: 38230 EAN: 4002888382304

© LINDY 2024