




Speaker, 2-way coax, **Hi-Fi**, **IP65*** waterproof.

LED technology.

69 points.

Watt 3.15.

Ansi Lumen 104.6L/m.

Temperature 3500K.

Power supply 12V 0.34A.

Dispersion 270°.

Warm white colour.

Woofer: 16.5 cm.

Tweeter: 2.5 cm.

Rated power at 70/100V: 7.5/15/30W RMS. 60 peak, max 97dB.

Power 8Ω: 40W RMS, 80W musical.

Recommended amplification: 10 to 60W RMS.

Impedance: 70V/100V - 8Ω selectable.

Frequency response 70-20000 Hz.

Sensitivity: 79dB. Max 97dB 1W/1mt.

Dimensions (WxHxD) 330x555x270 mm.

LED power supply (included).

VIVALDI

Weight 3.8kg.

Sand colour - RAL1013.

Cabinet: ABS polypropylene.

Degree of protection: IP65.

Dispersion angle: 360°(H)x40°(V).

Working temperature: -20° to +60°.

Vivaldi srl ongoing effort to improve its products, reserves the right to make technical and aesthetic changes effectively without obligation to notice



Images

Vivaldi Ulisse MOONLIGHT



Vivaldi srl

Via E. Fermi, 8 Z.I. EST - 30020 Noventa di Piave (Venezia) ITALIA
Tel. +39 0421 307825 - info@vivaldigroup.it - www.vivaldigroup.it

P.IVA e C.F. 02880360272