



Professional loudspeaker, **Hi-Fi** version, 3-way, with subwoofer.

IP66 protection. Ideal for outdoor applications even in marine areas. Resistant to corrosive agents such as chlorine and salt spray.

Provided with bracket for wall mounting.

Elliptical convex passive subwoofer 9x13 cm (WxH).

Woofer 10 cm polypropylene, graphite finish.

Tweeter 2.5 cm dome, neodymium and silk.

Dispersion angle 105°Vx90°H (120° up to 3 KHz).

Nominal power at 100V: 2.5/5/10/20W. 40W peak, max 100dB.

Power 8 Ω : 40W RMS, 80W musical.

Recommended amplification 10 to 60W RMS.

Impedance 8 Ω - 100V selectable.

Frequency response 65-20000 Hz.

Sensitivity 82 dB.

Max output level / full power 105 dB.

Dimensions (WxHxD) without bracket 140x212x140 mm.

Dimensions (WxHxD) with bracket 140x212x175 mm.

Weight 2.1 kg.

ABS enclosure, bracket and grille in painted aluminium.

Available colours white RAL 9003 with edges RAL7035 ([Vivaldi Ulisse ANNA10TW](#)) and black RAL9005 ([Vivaldi Ulisse ANNA10TB](#)).

VIVALDI

Working temperature -20° to +80°.

Vivaldi srl ongoing effort to improve its products, reserves the right to make technical and aesthetic changes effectively without obligation to notice



Images

Vivaldi Ulisse ANNA10T



Vivaldi srl

Via E. Fermi, 8 Z.I. EST - 30020 Noventa di Piave (Venezia) ITALIA
Tel. +39 0421 307825 - info@vivaldigroup.it - www.vivaldigroup.it
P.IVA e C.F. 02880360272