



100m Cat.6 HDMI 4K60, Audio, IR & RS-232 HDBaseT Extender

No.: 38340

Extend HDMI® resolutions up to 100m via HDBaseT

Description

- Distributes HDMI® resolutions up to 100m over Cat.6 network cable via HDBaseT technology
- Supports HDMI® 18G resolutions up to 4K@60Hz 4:4:4, with additional support for HDR
- ARC Support as well as RS-232, CEC & Ethernet pass-through & bi-directional IR for simple control
- Supports PoC (Power over cable), requiring a power supply connection from only one side of the installation
- 2 year warranty

The Lindy 100m Cat.6 HDMI® 4K60, Audio, IR & RS-232 HDBaseT Extender is a complete end to end high performance, reliable solution for extending HDMI signals over long distances via Cat.6 network cable.

The following distance and resolution combinations are possible when using high quality Cat.6 U/UTP or F/UTP cable:

100m: 1920x1080@60Hz 4:4:4 8bit

70m: 3840x2160@60Hz 4:4:4 8bit / 4:2:2 12bit

Supporting resolutions up to 4K Ultra HD, video can be viewed in stunning clarity, while additional support for HDR [High Dynamic Range] allows content to be displayed with enhanced brightness, greater contrasts of blacks and whites and a much wider colour gamut. This provides a reliable solution for creating eye-catching digital signage in retail, immersive displays at events or engaging setups in larger conference rooms or lectures halls.

ARC support over HDMI® allows for audio content to be returned from the display to a connected amplifier or soundbar, while local audio extraction allows for the connection of audio outputs for immersive multi-channel audio. Digital audio embedding at the receiver side can also be used for source audio, which can easily be switching via the push button on the main unit.

PoC [Power over Cable] functionality provides additional flexibility. This allows power to be supplied alongside data through Cat.6 network cable in a point-to-point connection between the transmitter and receiver, meaning only a single power supply is required at the transmitter unit. Ideal when power outlets are limited at the receiver end of the installation.

Featuring bi-directional IR ports at both sides of the setup, the source equipment can be easily controlled from the display side, and the display can also be controlled from the HDMI source side. Combined with CEC control, which allows commands from one main remote, this extension system allows for complete and simple control for the user. Bi-directional RS-232 and Ethernet ports also allow for integration into larger control systems, or connection to network switches and hubs with LAN access.

In addition, the power supply is connected via a screw type DC jack, providing a more secure and reliable connection,

perfect for professional installations where accidental disconnections could create a major issue. HDBaseT is a globally recognised standard for high quality distribution of AV content and other technologies, including power and control, over longer distances via low cost Cat.6 or above cable.

HDBaseT and the HDBaseT Alliance logo are trademarks of the HDBaseT Alliance. Using a different cable type, introducing wall plates, couplers or patch panels will result in a reduction of possible distances. Please Note: This product uses the DSC method of compression to achieve 18G resolutions. If using another 18G HDBaseT product combined with this, please ensure both products support the same compression type.

Technical details

Specifications

AV Interface: HDMI®
Interface Standard: HDMI® 2.0
Supported Bandwidth: 18Gbps
Maximum Distance:
70m [229.66ft] - 3840x2160@60Hz 4:4:4 8bit
100m [328.08ft] - 1920x1080@60Hz
Maximum Resolution: 3840x2160@60Hz 4:4:4 8bit
HDCP Support: 2.2
EDID Pass Through: Pass-through
Supported Audio: HDMI Audio Pass-through
TosLink (Optical) Up to 5.1Ch
3.5mm Up to 2.0Ch
Separate Audio Ports: TosLink (Optical), 3.5mm
IR Support: 20 - 60KHz
CEC Support: Pass-through
Serial Interface: RS-232
Transmission Protocol: HDBaseT
Transmission Medium: 1 x Cat.6
Laser Class (only for Fibre): -
Wavelength (only for Fibre): -
Chipset: VS2310TX-A1
Special Features: PoC (Power over Cable), ARC Support

Connectors

Transmitter Input: HDMI® Type A (Female), 3.5mm IR (Female)
Transmitter Output: RJ-45 (Female), TosLink (Optical) (Female), 3.5mm Audio (Female), 3.5mm IR (Female)
Receiver Input: RJ-45 (Female), Toslink (Optical) (Female), 3.5mm IR (Female)
Receiver Output: HDMI® Type A (Female), 3.5mm IR (Female)
Bi-directional Ports: RS-232 3-Pin Terminal Block, RJ-45 Ethernet (Female)
Power: 5.5/2.1mm

Physical Properties

Dimensions (approx.) WxDxH: 163x90x16mm [6.42x3.54x0.63in] per unit
Housing Material: Metal
Net Weight: 0.77kg [1.7lb]
Operating Temperature : 0°C - 40°C [32°F - 104°F]
Storage Temperature: -20°C - 60°C [-4°F - 140°F]
Humidity: 20 - 90% RH (non-condensing)
Power Requirements: 24VDC 1A
Colour: Black

Miscellaneous

Packaging Type: Carton Box
Packaging Dimensions: 265x70x210mm [10.43x2.76x8.27in]
Gross Weight: 1.28kg [2.82lb]
Warranty (Years): 2
Product Compliance: CE, UKCA, FCC, RoHS, REACH & California Proposition 65

Package Contents

Transmitter
Receiver
IR Emitter Cable, 1.5m
IR Receiver Cable, 1.5m
4 x Mounting Ears & 8 x Screws
2 x 3-Pin Terminal Block
Multi-country Power Supply (UK, EU, US & AUS)
Lindy Manual

Purchasing Information

No.: 38340
EAN: 4002888383400

