



4x4 HDMI 4K60 Matrix with Video Wall Scaling

No.: 38238

Seamlessly switch between 4 displays & 4 source devices, or create single or multiple video walls

Description

- Switches between 4 HDMI® source devices and 4 HDMI® displays as a professional matrix
- Creates classic video walls (up to 2x2) or vertical video walls (4x1)
- Seamlessly switch between devices under 0.1ms
- Control output scaling to ensure the optimum or consistent resolution is shown
- 2 year warranty

The Lindy 4x4 HDMI® 4K60 Matrix with Video Wall Scaling is the professional solution for distributing content from several source devices to many HDMI® displays, or for creating eye-catching video wall setups.

Supporting resolutions up to 4K@60Hz, content can be shown in excellent clarity, great for ensuring a high-quality video experience in sports bars, retail stores or multiple consecutive locations in larger installations. Resolutions can easily be scaled and controlled by the user to ensure the optimum, or consistent, resolution is always displayed.

As well as providing a professional 4x4 matrix switching function, this device can create customisable wall displays in a variety of layouts. This provides the user with a range of flexible display options for their installation and allows the device to be used in a range of specialised environments; including transport hubs, points of sale and hospitality. Analogue audio ports also allow for 2-channel audio extraction, to add immersive stereo audio to the content on screen.

The matrix also provides instant seamless switching between source devices and displays, a crucial feature for use in real time operation centre scenarios such as traffic monitoring, stock market floors or security setups. Controlled via independent IR as well as LAN and push button switching, this matrix ensures minimum effort is required of the user when creating their installation, while RS-232 control also allows for integration into larger control systems.

Professional EDID management ensures maximum compatibility with both the source devices and displays.

Technical details

Specifications

- AV Interface: HDMI®
- Interface Standard: HDMI® 2.0
- Supported Bandwidth: 18Gbps
- Maximum Resolution: 3840x2160@60Hz 4:4:4 8Bit
- HDCP Support: 1.4
- Supported Audio: HDMI® Audio Pass-through / 2CH Analogue Audio
- IR Support: 20-60kHz

CEC Support: Yes

Serial Interface: RS-232

LED / LCD Display: Yes

Control: IR, Push Button, RS-232, Software, Web GZU

Special Features: Seamless Switching, Video Wall Creation, Independant Audio Extraction, Independant IR Matrix

Connectors

Input: 4 x HDMI® Type A (Female), 4 x 3-Pin Phoenix (Female)

Output: 4 x HDMI® Type A (Female), 4 x 5-Pin Phoenix (Female), 4 x Mini Toslink (Female)

Control: RS232 (Female), RJ45 (Female). 8 x IR 3.5mm (Female)

Power: IEC C14 (Male)

Physical Properties

Dimensions [approx.] WxDxH: 430x220x44mm [16.93x8.66x1.73in]

Housing Material: Metal

Net Weight: 3.182kg [7.02lb]

Operating Temperature: 0°C - 40°C [32°F - 104°F]

Storage Temperature: -20°C - 70°C [-4°F - 158°F]

Humidity: 10 - 50% (non-condensing)

Power Requirements: 60W

Colour: Black

Miscellaneous

Packaging Type: Carton Box

Packaging Dimensions: 565x83x413mm [22.24x3.27x16.26in]

Gross Weight: 5kg [11.02lb]

Warranty (Years): 2

Product Compliance: CE, UKCA, FCC, RoHS & REACH

Package Contents

4x4 HDMI® Matrix

Multi-country C13 Power Cables, 2m

4 x IR Emitter Cables

4 x IR Receiver Cables

IR Remote & CR2025 Battery

1 x 3-Pin Phoenix Connector

1 x USB Type A to RS-232 Cable

Lindy Manual

Purchasing Information

No.: 38238

EAN: 4002888382380