



50m Cat.6 HDMI 4K60 & IR Extender with PoC & Loop Out

No.: 38205

Amplify HDMI® 18G & IR signals over 50m via Cat.6 cable

Description

- Extends 4K HDMI® 18G signals over 50m distances with standard network cable
- Supports resolutions up to 3840x2160@60Hz 4:4:4 8bit, with support for HDR
- An HDMI® loop-through output creates an additional viewing zone with a local display
- PoC (Power over Cable) functionality for power from a single power supply
- 2 year warranty

The Lindy Cat.6 HDMI® 4K60 & IR Extender with PoC is an effective, reliable solution for extending high quality 4K HDMI® signals over distances up to 50m [164.04ft] with standard Cat.5e/6 network cable. Support for the HDMI ® 2.0 18G specification allows the transmission of highly detailed 4K Ultra HD resolutions. With support for High-Dynamic Range, video content can be seen with enhanced brightness, greater contrasts of blacks and whites and a much wider colour gamut, perfect for a true home cinema experience or eye-catching digital signage in retail settings. HDCP 2.2 compliance allows 4K video content from copy protected sources such as Blu-Ray movies, media players and streaming services to be viewed without compatibility issues. Support for lossless audio formats including DolbyTrueHD and DTS-HD adds powerful multi-channel sound to video content, providing an enhanced experience and sense of realism for the viewer.

The extender features an HDMI® loop-through output on the transmitter which allows for simultaneous viewing using local and remote displays. This versatility provides a suitable solution for use in various scenarios such as educational presentation systems, home cinema, entertainment systems, or trade shows. The built in EDID dip switch enables the user to control which EDID is taken from either display, making installation and configuration simple ensuring maximum compatibility with HDMI® displays and projectors. PoC allows both power and data signals over a Cat.6 cable in a point to point configuration, adding flexibility as only one power supply is required for both the transmitter and receiver units. Ideal when power outlets are limited.

Featuring IR Pass-through, the source equipment can be seamlessly controlled from the remote displays side of the installation using compatible infrared remote controls. This provides simple and complete control for the user.

Please note: This product is not designed to be used in conjunction with active network equipment and must only be used in a point to point connection.

Technical details

Specifications

- AV Interface: HDMI®
- Interface Standard: HDMI® 2.0

Supported Bandwidth: 18Gbps
Maximum Distance: 50m [164.04ft] Cat.6/7, 30m [98.42ft] Cat.5e
Maximum Resolution: 3840x2160@60Hz 4:4:4 8bit
HDCP Support: Pass-through
EDID Pass Through: Pass-through
Supported Audio: Up to 7.1 [Pass-through]
Separate Audio Ports: -
IR Support: 20-60kHz
CEC Support: -
Serial Interface: -
Transmission Protocol: -
Transmission Medium: 1 x Cat.5e/6 or higher
Laser Class (only for Fibre): -
Wavelength (only for Fibre): -
Chipset: Transmitter: SIL9396 / Receiver: SIL9630
Special Features:
 PoC [Power over Cable]
 IR Pass-through
 Loop Out

Connectors

Transmitter Input: HDMI® Type A 19pin [Female], Micro-USB [Female], DC12V Power
Transmitter Output: HDMI® Type A 19pin [Female], RJ45 [Female], IR [Female]
Receiver Input: RJ45 [Female], IR [Female], Micro-USB [Female]
Receiver Output: HDMI® Type A 19pin [Female]
Bidirectional Ports: -
Power: 5.5/2.1mm barrel size

Physical Properties

Dimensions [approx.] WxDxH:
 Transmitter: 70x97x15mm [2.76x3.82x0.59in]
 Receiver: 70x97x15mm [2.76x3.82x0.59in]
Housing Material: Metal
Net Weight:
 Transmitter: 0.156kg [0.34lb]
 Receiver: 0.151kg [0.33lb]
Operating Temperature: 0°C - 40°C [32°F - 104°F]
Storage Temperature: -20°C - 60°C [-4°F - 140°F]
Humidity: 20 - 90% RH [no condensation]
Power Requirements: 12VDC 1A
Colour: Black

Miscellaneous

Packaging Type: Carton Box
Packaging Dimensions: 220x130x70mm [8.66x5.12x2.76in]
Gross Weight: 0.605kg [1.33lb]
Warranty [Years]: 2
Product Compliance: CE, FCC, RoHS, REACH & California Proposition 65

Package Content

Transmitter
Receiver
12VDC 1A Multi-country Power Supply [UK, EU, US & AUS]
IR Transmitter
IR Receiver
Mounting kit with 4x brackets and 8x screws
Lindy Manual

Purchasing Information

No.: 38205
EAN: 4002888382052