



## 4x2 HDMI 4K60 Matrix

No.: 38084

Connect and switch between 4 HDMI® source devices and 2 HDMI® displays

### Description

- Switches between 4 HDMI® source devices and 2 HDMI® displays connected simultaneously
- Supports resolutions up to 4K 60Hz, with additional support for HDR
- Extract audio from HDMI® to Toslink [Optical] and 3.5mm audio
- Supports ARC as well as a Downscaler-Function via HDMI® Out B
- 2 year warranty

The Lindy 4x2 HDMI® 4K60 Matrix Switch is a high performance solution for distributing content from multiple source devices to two displays.

Supporting HDMI® 2.0 18G signals, this matrix allows for the transmission of clear 4K Ultra HD 60Hz resolutions, while additional support for High Dynamic Range ensures video content can be seen with enhanced brightness, greater contrasts and a much wider colour gamut, perfect for digital signage displays in retail or hospitality or creating engaging educational setups. HDCP 2.2 support ensures there are no issues with a variety of 4K content when connected to source devices including set top boxes, Blu-Ray players and 4K HDR media players.

As well as HDMI® audio pass-through, a 3.5mm audio port allows for a separate connection of both analogue speaker systems, and optical audio devices such as soundbars and amplifiers, for creating immersive audio experiences to compliment the video on screen.

This matrix can be easily controlled via push button switching on the unit, while the included remote control also allows the user to have better control over multiple videos and displays, great for trade shows, training presentations or sales demonstrations.

### Technical details

#### Specifications

- AV Interface: HDMI®
- Interface Standard: HDMI® 2.0
- Supported Bandwidth: 18Gbps
- Maximum Resolution: 3840x2160@60Hz 4:4:4 8bit
- HDCP Support: 2.2
- Supported Audio:
  - HDMI® Audio Pass-through
  - Toslink [Optical] Up to 5.1CH
  - Stereo Analogue
- IR Support: 38kHz

CEC Support: -  
Serial Interface: -  
LED / LCD Display: -  
Control: Push Button, IR  
Special Features: EDID Management, ARC Support, 4K - 1080p Downscaling Functionality, Dual Audio Extraction

#### **Connectors**

Input: 4 x HDMI® (Female)

Output:

2 x HDMI® (Female)

2 x 3.5mm (Female)

2 x Coaxial (Female)

2 x TosLink (Optical) (Female)

Control: -

Power: 3.5/1.35mm

#### **Physical Properties**

Dimensions (approx.) WxDxH: 210x66x26.5mm (8.27x2.6x1.04in)

Housing Material: Metal

Net Weight: 0.348kg (0.77lb)

Operating Temperature: 0°C - 70°C (32°F - 158°F)

Storage Temperature: -10°C - 80°C (14°F - 176°F)

Humidity: 5 - 90% RH (non-condensing)

Power Requirements: 5VDC 2A

Colour: Black

#### **Miscellaneous**

Packaging Type: Carton box

Packaging Dimensions: 243x60x196mm (9.57x2.36x7.72in)

Gross Weight: 0.636kg (1.4lb)

Warranty (Years): 2

Product Compliance: CE, UKCA, FCC, RoHS, REACH & California Proposition 65

#### **Package Contents**

HDMI® Matrix

IR Remote Control & CR2025 Battery

Multi-Country Power Supply (EU, UK, US & AUS)

Lindy Manual

#### **Purchasing Information**

No.: 38084

EAN: 4002888380843