



60m Fibre Optic Hybrid HDMI 8K60 Cable No.: 38516

AOC cable for every HDMI application and resolution

Description

Combines copper and fibre optic cable for a hybrid, long distance HDMI connectivity solution Supports resolutions up to 4K@120Hz, 8K@60Hz HDR formats including Dolby Vision & HDR10+ Flexible and robust cable structure for any kind of installations 2-Year Warranty

Lindy's range of Fibre Optic Hybrid cables are a professional solution for extending HDMI signals over longer distances. Combining the flexibility and high EMI & RFI resistance of fibre optic cable with standard copper cabling, these hybrid cables are ideal for use in critical AV setups, commercial displays or high-performance residential installations.

The internal technology provides uncompressed amplification of the HDMI signal, allowing long distance extension of HDMI 8K content that is simply not possible with passive cables.

With 48Gbps bandwidth, these cables support HDMI 2.1 resolutions up to 3840x2160@120Hz, and 7680x4320 / 10240x4320@60Hz. Content can be viewed with incredible detail and clarity at higher refresh rates for optimum viewing of movies, graphics or imagery.

As well as static HDR, HDMI hybrid cables also brings further support for dynamic HDR formats such as Dolby Vision and HDR10+. This provides every moment of content, whether scene by scene or even frame by frame, with a much wider colour gamut based on the BT.2020 colour space, higher peak brightness and deep blacks for optimum contrasts as well as greater depth of colour. This is essential for the transmission of VOD content including TV shows and movies, as well as VR and video games, ideal in eSports, retail setups and superior home cinema installations.

Please Note: eARC/ARC and CEC functions are not supported for lengths over 20m. We can make cables up to 200m on request, contact us for quotations.

Technical details

Connectors

Connector A: HDMI Type A (Male) Connector B: HDMI Type A (Male) Housing Material: PVC Connector Plating: Gold Plated Pin Construction: Gold Plated Pin Plating: Gold Plated Dimensions (approx.) WxDxH: HDMI Connector: 20.2x50.5x11mm (0.8x1.99x0.43in) **Cable Construction** Length: 60m (196.85ft) Standard: HDMI 2.1 Colour: Black Type: Round Jacket Diameter: 4.4mm (0.17in) Jacket Material: PVC Conductor Material: Fiber and Copper Conductor Gauge: 23AWG Shielding: -Specifications Supported Bandwidth: 48Gbps Maximum Resolution: 7680x4320@60Hz 4:2:0 10bit, 3840x2160@120Hz 4:4:4 10bit Nominal Attenuation: _10dB/km@850nm, _8dB/km@1300nm Minimum Bend Radius: 50mm (1.97in) Operating Temperature: -10°C - 60°C (14°F - 140°F) Storage Temperature: -20°C - 70°C (-4°F - 158°F) Miscellaneous Packaging Type: Carton Box Warranty (Years): 2 Certificated: CE, UKCA, FCC, RoHS, REACH & California Proposition 65 **Purchasing Information** No.: 38516 EAN: 4002888385169 This product is also available in other lengths: 38511 - 15m (49.21ft) 38512 - 20m (65.62ft) 38513 - 30m (98.42ft) 38514 - 40m (131.23ft) 38515 - 50m (164.04ft) 38517 - 70m (231.95ft) 38518 - 100m (328.41ft)

© LINDY 2024